

应用领域

- 用户侧C&I工商业储能的峰谷套利, 后备电源;
- 风光新能源电站的削峰填谷平滑输出;
- 电网侧调频调峰, 配电网变压器容量扩容



全舱温差
 $<5^{\circ}\text{C}$



三级消防
高安全性



高能量密度
灵活布置及扩容



模块化预制
无需现场安装

参数/型号		EnerGalactic-2418-Na
电池模块	电芯容量	170Ah(Na ⁺)
	模块成组	1P52S
	模块标称电压	148.2V
	模块能量	25.194kWh
	防护等级	IP67
电池簇	模块数量	8pcs
	电池簇标称电压	DC1185.6V
	电压范围	624~1456V
	单簇能量	201.552kWh
电池舱	电池簇数量	12pcs
	电池系统电量	2418kWh
	电池舱尺寸(W*D*H)	6058*2438*2896mm
	重量	≤43t
	冷却方式	液冷
	防护等级	IP54
符合标准	Cluster	IEC62619、UL1973、UL9540A、UN38.3



昆宇电源股份有限公司

网址:WWW.COSPOWERS.COM

地址:山东省东营市东营区东七路28号

电话:0546-7768891

版权及最终解释权归昆宇电源股份有限公司所有

Application Field

- Post-meter electricity market, peak-valley arbitrage and backup power supply of C&I (commercial and industrial) energy storage on the customer side.
- Peak shaving and valley filling for smooth output of wind and solar new energy power stations.
- Grid frequency regulation and peak load regulation in the pre-meter electricity market, as well as capacity expansion of distribution network transformers.



Temperature Difference
inside the Battery
Pack: <5°C



Triple-level Fire
Protection for
High Safety



High Energy Density
for Flexible Layout
and Expansion



Modular Prefabrication
No On-site Installation
Required

Parameters/ Model		EnerGalactic-2418-Na
Battery Module	Cell Capacity	170Ah(Na ⁺)
	Battery Pack	1P52S
	Module Voltage	148.2V
	Module Power	25.194kWh
	IP Class	IP67
Battery Cluster	Nos.of Modules	8pcs
	Cluster Nominal Voltage	DC1185.6V
	Voltage Range	624~1456V
	Single Cluster Power	201.552kWh
Battery Cabin	Nos. of Battery Clusters	12pcs
	Battery system energy	2418kWh
	Battery Cabin Dimension(W*D*H)	6058*2438*2896mm
	Weight	≤43t
	Cooling Method	Liquid cooling
	IP Class	IP54
Compliant with Standards	Cluster	IEC62619、UL1973、UL9540A、UN38.3



Cospowers Technology Co., Ltd.

W:WWW.COSPOWERS.COM

A:No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T:+86-546-7768891

Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.